

Pumpeunit

Datablad 06/16

Skreddarsydd til notvaskar for optimal drift. Sjølvforsynt, komplett eining med vasskjølt dieselmotor. Lyddempa kabinett.



Spesifikasjonar

INNDELING	DEL	SPESIFIKASJONAR
Samla utstyr	karosseri og plattform	Lydisolert stålkabinett med trucklommer, løftepunkt på topp
	Ytre mål mm (LxBxH)	Ca. 3500 x 1200 x 2255
	Samla vekt	Ca. 2500 kg (tørr)
Motor	Motormodell	FTP Iveco NEF67 TM 3A
	Type	Firetakts vasskjølt dieselmotor
	Slagvolum	6,7 L
Høgtrykkspumpe	Nominelt leveringstrykk	170 bar
	Nominell omdreiningshastighet	1500 rpm
	Nominelt leveringsvolum	330 l/min
	Fødepumpe	2 x Jabsco 52270-Series impellerpumpe
Drivstofftank	Type	Plasttank, plassert nederst i kabinett
	Totalkapasitet	226 Liter
CE-merka		





Pump unit

Data sheet 06/16

Custom made to suit the netcleaners needs. Stand alone, complete solution with water-cooled diesel engine. Sound proofed cabinet.



Speks

PARTS		SPEKS.
Equipment	Body and platform	Sound proofed steel cabinet with forklift pockets, single lifting lug on top
	Outer measures mm (LxWxH)	Ca. 3500 x 1200 x 2255
	Total weight	Ca. 2500 kg (dry)
Motor	model	FTP Iveco NEF67 TM 3A
	Type	Four stroke water-cooled diesel engine
	Slagvolum	6,7 L
High pressure pump	Nominal supply pressure	170 bar
	Nominal rotational speed	1500 rpm
	Nominal delivery volume	330 l/min
	Feed pump	2 x Jabsco 52270-Series impeller pump
Fuel tank	Type	Plastic
	Total capacity	226 Liter
CE approved		



Østerbo Maskin AS, Østerbo, 5962 BJORDAL



+47 48 16 17 18



om@osterbo.no



osterbo.no



Føretaksreg.: 976 195 922 MVA