

Hydro mower RM9



Technical data – basic equipment:

Engine: 4-stroke petrol engine SUBARU ROBIN EX27, OHV, 6,6 kW / 9 hp, 265 cm³ displacement, fuel pump, recoil starter

Tyres: AS 4.00-10

Optional: BR 18x9.50-8 / RB 18x7.00-8 / RB 4.00-10 / AS 5.00-10 / RB 20x8.00-10

Clutch: Electromagnetic clutch (on/off)

Travel drive: Hydrostatic, continuous speed control forward and reverse

Speed control: Two-piece rotary handle

Speed: 0-6 kph forward, 0-4 kph reverse

Freewheel: Hydraulic freewheel switching, manoeuvrable (not for towing)

Parking brake: Mechanical

Steering: Differential axle with lock

Bar height adjustment: Fine incrementation via notch system

Bar lateral adjustment: 50° both sides

Swivelling bar: 180° swivelling for use with rotary how

PTO: 872 rpm at 3200 rpm engine speed


Attachment mounting shaft: 52 / 54 mm, stepped connection shank for toolless quick attachment change

Accessories: Twin wheels, steel cage wheel, spike wheels, Electric starter (only in original equipment)

Attachments: Finger cutter bar 130-160 cm, Brush cutting bar 130-160 cm, Municipal cutter bar 122-162 cm, Flail mulcher 68 cm, Sickle mower unit 105 cm, Eco mulcher 80 cm, Universal power harrow 75 cm, top-mounted seed drill 75 cm, Rotary hoe 70 cm, reversing rotary hoe 70 cm, Combination road sweeper 90-110 cm, Leaf vacuum with turbine and accessories 75 cm, Snow blade 100-125 cm, snow blower 70 cm, Salt, grit and sand spreader 70 l, Combined sprayer 85 l, Other attachments on request

Weight: Basic unit from 130 kg

Dimensions:



Tyres AS 4.00-10

Twin wheel AS 4.00-10 (flange 60 mm)

Steel cage wheel (flange 60 mm)

* Wheel narrow / wide position